



# PAINT SAFETY DATA SHEET



## SAFETY DATA SHEET

BRUNDLE RED OXIDE PAINT

Page: 1

Compilation date: 26/06/2018

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** BRUNDLE RED OXIDE PAINT

**Product code:** 29BRO025

**Synonyms:** RED OXIDE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** F.H. BRUNDLE  
24-36 LAMSON ROAD  
FERRY LANE NORTH  
RAINHAM  
ESSEX  
RM13 9YY  
UK

**Tel:** +44 (0) 1708 25 35 45

**Fax:** +44 (0) 1708 25 35 50

**Email:** sales@brundle.com

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1282 834545      Mon-Fri 08:30-16:30      [www.fhbrundle.co.uk](http://www.fhbrundle.co.uk)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** F: R11; Xn: R20/21; Xi: R38; Xn: R40; Sens.: R43; N: R51/53

**Classification under CLP:** Eye Irrit. 2: H319; Aquatic Chronic 2: H411; Carc. 2: H351; Flam. Liq. 2: H225; Skin Irrit. 2: H315

**Most important adverse effects:** Highly flammable. Harmful by inhalation and in contact with skin. Irritating to skin.  
Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.2. Label elements

##### Label elements under CLP:

**Hazard statements:** H225: Highly flammable liquid and vapour.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H351: Suspected of causing cancer.  
H411: Toxic to aquatic life with long lasting effects.

[cont...]

# SAFETY DATA SHEET

## BRUNDLE RED OXIDE PAINT

Page: 2

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



**Precautionary statements:** P202: Do not handle until all safety precautions have been read and understood.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

P280: Wear.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical.

P370+378: In case of fire: Use for extinction.

### Label elements under CHIP:

**Hazard symbols:** Highly flammable.

Harmful.

Dangerous for the environment.



**Risk phrases:** R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S36/37: Wear suitable protective clothing and gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This substance is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

[cont...]

**SAFETY DATA SHEET**  
BRUNDLE RED OXIDE PAINT

Page: 3

**Hazardous ingredients:**

ALKYD RESIN SOLUTION

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	-: R10; Xn: R20/21; Xi: R38	-	30-50%

XYLENE

215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	-----------------------------	--	-------

ZINC PHOSPHATE

231-944-3	7779-90-0	N: R50/53	-	1-10%
-----------	-----------	-----------	---	-------

10% COBALT DRIER

-	-	Xn: R22; Xi: R38; Sens.: R43; Xn: R65	-	<1%
---	---	--	---	-----

10% CALCIUM DRIER

-	-	Xi: R38	-	<1%
---	---	---------	---	-----

METHYL ETHYL KETOXIME

202-496-6	96-29-7	Xn: R21; Xn: R40; Xi: R41; Sens.: R43	-	<1%
-----------	---------	--	---	-----

**Section 4: First aid measures**

**4.1. Description of first aid measures**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Not applicable.

[cont...]

**SAFETY DATA SHEET**  
BRUNDLE RED OXIDE PAINT

Page: 4

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Do not handle in a confined space. Avoid the formation or spread of mists in the air.  
Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.  
Ensure lighting and electrical equipment are not a source of ignition.

[cont...]

**SAFETY DATA SHEET**  
BRUNDLE RED OXIDE PAINT

Page: 5

**7.3. Specific end use(s)**

Specific end use(s): No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**XYLENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	-	-

**ZINC PHOSPHATE**

UK	10 mg/m3	-	-	-
----	----------	---	---	---

**10% CALCIUM DRIER**

UK	1000 mg/m3	-	-	-
----	------------	---	---	---

**METHYL ETHYL KETOXIME**

UK	10 mg/m3	-	-	-
----	----------	---	---	---

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Red

**Viscosity:** Viscous

**Boiling point/range°C:** >35

**Flash point°C:** <21

**pH:** Approx. 7

**9.2. Other information**

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

[cont...]

**SAFETY DATA SHEET**  
BRUNDLE RED OXIDE PAINT

Page: 6

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Relevant effects for mixture:**

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** Not applicable.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

[cont...]

**SAFETY DATA SHEET**  
BRUNDLE RED OXIDE PAINT

Page: 7

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This substance is not identified as a PBT substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1263

**14.2. UN proper shipping name**

**Shipping name:** PAINT

**14.3. Transport hazard class(es)**

**Transport class:** 3

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** Yes

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 3

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

[cont...]

**SAFETY DATA SHEET**  
BRUNDLE RED OXIDE PAINT

Page: 8

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and 3:** H225: Highly flammable liquid and vapour.  
H226: Flammable liquid and vapour.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H411: Toxic to aquatic life with long lasting effects.  
R10: Flammable.  
R11: Highly flammable.  
R20/21: Harmful by inhalation and in contact with skin.  
R21: Harmful in contact with skin.  
R22: Harmful if swallowed.  
R38: Irritating to skin.  
R40: Limited evidence of a carcinogenic effect.  
R41: Risk of serious damage to eyes.  
R43: May cause sensitisation by skin contact.  
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65: Harmful: may cause lung damage if swallowed.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]

Whilst every effort has been made to ensure the accuracy of the information supplied, F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

**Southampton**  
Tel: 023 8070 3333  
Fax: 023 8070 5555

**Rainham**  
Tel: 01708 25 35 45  
Fax: 01708 25 35 50

**Ilkeston**  
Tel: 0115 930 2070  
Fax: 0115 951 2455

**Birmingham**  
Tel: 0121 565 8282  
Fax: 0121 565 8292

**Haydock**  
Tel: 01942 86 88 88  
Fax: 01942 86 88 99

**Glasgow**  
Tel: 0141 773 6699  
Fax: 0141 773 6633



**F.H.BRUNDLE**  
SERVING THE TRADE SINCE 1889

**www.fhbrundle.co.uk**  
**sales@brundle.com**