



A double inline swivel connector. Typically used on sloping guardrail. This fitting combines 1 x 167M & 2 x 173F. The swivels can travel approximately 85° from the horizontal in both directions. **THIS FITTING IS NOT DESIGNED TO WITHSTAND LATERAL LOADINGS. AN ENTIRE STRUCTURE SHOULD NOT BE BUILT USING ONLY SWIVEL FITTINGS, THIS WOULD BE UNSTABLE.**

PART CODE	MATERIAL	TUBE SIZE Ø	A	B	C	FINISH
16167A	Malleable Cast Iron	26.9	53mm	40mm	39mm	Galvanised
16167B	Malleable Cast Iron	33.7	60mm	44mm	41mm	Galvanised
16167C	Malleable Cast Iron	42.4	63mm	49mm	44mm	Galvanised
16167D	Malleable Cast Iron	48.3	70mm	52mm	50mm	Galvanised
16167E	Malleable Cast Iron	60.3	95mm	63mm	70mm	Galvanised

DESCRIPTION: TubeClamp Double Swivel Combination						
	NAME	DATE	REVISION	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS		A3
DRAWN	TS	24/03/2022	A			
CHECKED				DO NOT SCALE DRAWING	SCALE:1:1	