

F H Brundle Paints & Coatings

Product Code: 2904P

Fast Dry Red Oxide Primer

- Description: The main features of this product are:
- 1) Economical in use.
 - 2) Excellent Obliteration.
 - 3) Rapid Drying.
- General: Fast Dry Red Oxide Primer is a general purpose, low-cost primer for use on suitably cleaned steel. It is based on a special alkyd resin which ensures rapid dry along with adhesion and toughness.
- Surface Preparation: Surfaces should be thoroughly cleaned and free from rust, mill-scale and grease.
- Application: The primer is intended for application by spray, but with suitable adjustment and care, brush application over limited areas is possible.
- Thinning: For best results Brundle 29002 Thinners should be used for any necessary adjustment to viscosity and also for clean-up.
- Coverage: Spreading rate will vary with the method of application. In normal circumstances, this should be of the order of 8-10 square metres per litre (theoretical).
- Film Thickness: Film thickness will also vary with application, but, at normal spreading rates the following should apply:
- Wet Film Thickness: Approx. 75 microns.
Dry Film Thickness: Approx. 25-30 microns.
- Volume Solids: 45%
- Drying: Under normal working conditions, appropriate drying times are as follows:
Surface dry: Approx. 30 minutes
Hard dry: 4-6 hours
- Over-coating Time: 16-24 hours

Finishing: The primer is suitable for finishing out with most decorative and general industrial finishes. In certain circumstances, it may be advisable to carry out preliminary tests in order to confirm compatibility.

Packages: Available in 5 litre and 20 litre containers.

Precautions: Flammable.
Keep away from sources of ignition - NO SMOKING
Use only in well ventilated areas.
Avoid contact with skin and eyes.
In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
In case of contact with skin rinse immediately with plenty of a recognised skin cleaner or soap and water.
In case of insufficient ventilation, wear suitable respiratory equipment.
Do not breathe vapour or spray.
Keep out of reach of children.

ALWAYS STIR WELL BEFORE USE

Disclaimer: The information given in this sheet is not intended to be exhaustive and any person(s) using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose does so at his own risk.

Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising from the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and possible product development.

It is the user's responsibility to check that this sheet is current prior to using the product.

F H Brundle,
Lamson Rd.,
Ferry Lane North,
Rainham,
Essex
RM13 9YY

Tel: 01708 253545
Fax: 01708 253550
Email: sales@brundle.com
Web: www.fhbrundle.co.uk

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H.Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Application must be carried out in full compliance with current regulations. Please consult the relevant Safety Data Sheet (SDS) for further information. F.H.Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.



F.H.BRUNDL
SERVING THE TRADE SINCE 1889

www.fhbrundle.co.uk
sales@brundle.com