# **TECHNICAL DATA SHEET**



### **PRODUCT NAME**

## 29BESB025 – Brushable Black Satin Enamel

#### **PRODUCT DESCRIPTION**

A Black Satin Enamel paint that is a very hard and durable, with excellent resistance to petrol, paraffin and mineral oils. Used regularly on products that are subjected to heavy wear, such as machinery.

#### **AVAILABILITY**

This product is available in 2.5ltr packs.

#### **FURTHER INFORMATION**

This product is specifically designed to be brushed or rolled. Can be thinned by up to 10% maximum. If overcoating is required, 24 hours minimum before application.

VISCOSITY	SPECIFIC GRAVITY	GLOSS
6-8 Poise @ Roto 20c	1.12-1.16 SPL	35-45%

#### SURFACE PREPERATION AND APPLICATION

Ensure surface has already been primed prior to application of product. Make sure primed surface is free from dust, grease or any other contamination.

APPLICATION AIRLESS SPRAY Brush or Foam Roller.

#### **HEALTH & SAFETY**

Refer to M.S.D.S. 29BESB025 prior to use. See: <u>https://www.fhbrundle.co.uk/files/file/sds/29BESB025.pdf</u>

Provide adequate ventilation.

Prolonged skin contact and inhalation of vapour must be avoided.

Eye contamination - Flush with eyewash or warm water for 10 mins.

Clean hands after use.

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and F.H. Brundle can accept no liability for the performance of the product or for any loss or damage arising out of such use.

FLASH POINT 32-55°C VOC: 530 g/litre VOLUME SOLIDS 37% ( -/+ 2%) THINNERS 29WS05 White Spirit SHELF LIFE 12 Months

**RECOMMENDED W.F.T.** 

**RECOMMENDED D.F.T.** 

125-150 microns

40-60 microns

THEORETICAL

**SPREADING RATE** 

10-12 Sq. Metres/Litre

**DRYING TIME @ 20°C** 

Surface Dry: 6-8 hours

Issued: 19/01/2022

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

	<b>F.H.BRUNDLE</b> SERVING THE TRADE SINCE 1889		www.fhbrundle.co.uk sales@brundle.com		
Fax: 023 8070 5555	Fax: 01708 25 35 50	<b>Fax: 0115 951 2455</b>	Fax: 0121 565 8292	Fax: 01942 86 88 99	Fax: 0141 773 6633
Tel: 023 8070 3333	Tel: 01708 25 35 45	Tel: 0115 930 2070	Tel: 0121 565 8282	Tel: 01942 86 88 88	Tel: 0141 773 6699
Southampton	Rainham	likeston	Birmingham	Haydock	Glasgow