# TECHNICAL DATA SHEET



## **PRODUCT NAME**

Spray can topcoats for touch up

## PRODUCT DESCRIPTION

F.H Brundle supply a wide variety of aerosol spray cans which are available to help the customer finalise their finishing coat. These are used to cover any hard to reach places, plus to repair any small areas of damage which may have occurred during movement, transport or installation of goods.

#### **AVAILABILITY**

This product is a 400m rattle can.

## **FURTHER INFORMATION**

On the next page is a list of all relevant spray cans supplied with relevant details.

\*Due to the protective nature of the coating, some chalking may occur on exposure/weathering. This is aesthetic and will not deter from the performance of the product.

## SURFACE PREPERATION AND APPLICATION

Ensure surface is free from rust, moisture, oil, or other surface contamination.

#### **APPLICATION**

Product should be applied at least 20cm away from surface and sprayed continuously at a fanning angle. To clean the nozzle, turn can upside down and spray until passageway is clear.

#### **HEALTH & SAFETY**

Refer to Spray can M.S.D.S. prior to use. These can be found under the relevant Product Codes on <a href="https://www.fhbrundle.co.uk/">https://www.fhbrundle.co.uk/</a>

Provide adequate ventilation. Prolonged skin contact inhalation of vapour must be avoided.

Eye contamination - Flush with eyewash or warm water for 10 mins.

Always clean hands after use.

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and F.H. Brundle can accept no liability for the performance of the product or for any loss or damage arising out of such use.

RECOMMENDED W.F.T.

N/A

RECOMMENDED D.F.T.

N/A

THEORETICAL SPREADING RATE

1.5-3 Sq. Metres/Litre

**DRYING TIME @ 20°C** 

Surface Dry: 10-20 minutes

**FLASH POINT:** 

VOC: N/A

**VOLUME SOLIDS:** N/A

**THINNERS:** N/A

**SHELF LIFE:** 12 Months

PRODUCT CODE	PRODUCT NAME	COLOUR	GLOSS LEVEL
29RSBS	Smithy Black Semi-Gloss Vinylast	Black	20-30%
29RMBS	Smithy Matt Black Vinylast	Black	<5%
29RGBS	Smithy Gloss Black Vinylast	Black	>70%
29RSWS	Smithy White Vinylast	RAL 9010	20-30%
29PC400SG	Fortitude Green Gloss Aerosol	RAL 6005	40-50%
29PC400SB	Fortitude Black Gloss Aerosol	RAL 9005	40-50%
29PC400SBS	Fortitude Black Sand Aerosol	Specialist	40-50%
29PC400SW	Fortitude White Gloss Aerosol	RAL 9010	40-50%
29PC400SSY	Yellow Gloss	RAL 1003	>70%
29PC400SA	Anthracite Gloss	RAL 7012	>70%
29PC400SAM	Basalt Matt	RAL7012	<5%
29PC400SLS	Light Sage Matt	RAL 7032	<5%
29PC400SUG	Umbra Matt	RAL 7022	<5%
29PC400SMG	Mineral Grey Matt	RAL 7045	<5%
29PC400SSS	Serengeti Sand Matt	RAL 1019	<5%
29PC400SOW	Oyster White Matt	RAL 1013	<5%
29PC400SMG	Mineral Grey Matt	RAL 7045	<5%
29PC400STB	Terra Brown Matt	RAL 7028	<5%
29PC400SSSG	Serengeti Sand Gloss	RAL 1019	>70%
29PC400SSSY	Serengeti Sand Synergised	RAL 1019	<5% (textured)
29PC400SBSY	Black Synergised	RAL 9005	<5% (textured)
29PC400SASY	Anthracite Synergised	RAL 7016	<5% (textured)

12/05/2022

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

Southampton Tel: 023 8070 3333 Fax: 023 8070 5555 Rainham Tel: 01708 25 35 45 Fax: 01708 25 35 50 Ilkeston Tel: 0115 930 2070 Fax: 0115 951 2455 Birmingham Tel: 0121 565 8282 Fax: 0121 565 8292 Newton-Le-Willows Tel: 01942 86 88 88 Fax: 01942 86 88 99 Glasgow Tel: 0141 773 6699 Fax: 0141 773 6633



F.H.BRUNDLE SERVING THE TRADE SINCE 1889 www.fhbrundle.co.uk sales@brundle.com