

TECHNICAL DATA SHEET



PRODUCT CODE: 2902L LIGHT ZINC (Z350)

DESCRIPTION

F.H. Brundle offers a series of specific products for galvanising. This spray is ideal for protecting steel or repairing or touching up galvanised surfaces.



Quantity	400 ml
Confection	12 pz

LIGHT ZINC - Cold galvanise spray with a high molecular weight, it chemically solidifies producing a long lasting metal coating. It protects all metal surface from oxidation. It forms an even corrosion resistant layer which can be painted or left as a final protection. It is ideal for retouching, for final finish and repairing of galvanised parts.

TECHNICAL SPECIFICATIONS:

Aspect	Tin-plate can containing under pressure fluid
Temperature resistance	400° C
Colour	Light brown
Odour	Characteristic of solvent
Relative density	a 20° C 0,75 ÷ 0,80 g/ml
Flash point	0° C
Percentage of zinc on dry residual	10%
Drying times	Touch dry: 20 minutes
Pressure at 20C	4/6 bar

STORAGE

Before using: stock the product in a dry location. Do not store at temperatures below 0° C. After use, keep containers closed. In the original package, the product can be stored for 24 months. After the first usage: Store in a ventilated, dry location and away from heat sources. Keep out of reach of children.

HAZARDS IDENTIFICATION:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H319 Causes serious eye irritation.

Toxic to aquatic life with long-lasting effects. H410

EUH066 Repeated exposure may cause skin dryness or cracking.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, including the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

