



Wholesale Distributors since 1889



Securifor® Super 6

The highest level of security panel within the Securifor® range. This NEW panel incorporates 6mm vertical wires to give maximum resistance to cut through attacks. Features a toe and finger-proof mesh and combines an anti-climb and anti-cut fence with excellent through visibility. Maximum security for schools, industrial and commercial premises through to secure units and prisons.

Specification

Mesh Pattern	76.2mm x 12.7mm resistance welded at each intersection
Horizontal Wires	4mm dia at 12.7mm centres
Vertical Wires	6mm dia at 76.2mm centres
Weld strength	75% of the minimum tensile strength of the wire
Finish	Polyester coated with a galvanised substrate
Presentation	Overlapped 75mm minimum at each post for securing with slotted clamp bars and M8 dia cup square round bolts

Fence Height m	Panel Size Height/Width mm	Fence Height m	Panel Size Height/Width mm
1.27	1270 x 2515	3.6	3800 x 2515
2.4	2400 x 2515	4.0	4000 x 2515
2.7	2700 x 2515	4.5	4500 x 2515
3.0	3000 x 2515	4.8	4800 x 2515
3.3	3300 x 2515	5.2	5200 x 2515

Securifor® 358/Super 6 Bolt Through Posts

Posts come complete with clamp bar fittings and black plastic top caps.
Polyester coated with a galvanised substrate.

Posts:

Section sizes	2.4m high	80 x 80 x 2.5mm
	2.7m high	80 x 80 x 2.5mm
	3.0m high	80 x 80 x 2.5mm

Fence Height m	Overall Length mm	Intermediate Post		
		Weight Kgs	Number of fixings	Product Code
2.4	3100	13.95	9	58BTP24I
2.7	3400	20.64	10	58BTP27I
3.0	3800	23.07	11	58BTP30I

Fence Height m	Overall Length mm	Corners		
		Weight Kgs	Number of fixings	Product Code
2.4	3100	13.95	18	58BTP24C
2.7	3400	20.64	20	58BTP27C
3.0	3800	23.07	22	58BTP30C

Sheer cone nuts available upon request