

PAINT SAFETY DATA SHEET



SAFETY DATA SHEET

MOSS GREEN VINYLAST

Page: 1 Compilation date: 26/07/2018

www.fhbrundle.co.uk

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: MOSS GREEN VINYLAST

Product code: 29RSMG025

Synonyms: MOSS GREEN

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	FH BRUNDLE		
	24-36 LAMSON ROAD		
	FERRY LANE NORTH		
	RAINHAM		
	ESSEX		
	RM13 9YY		
	UK		
Tel:	+44 (0) 1708 25 35 45		
Fax:	+44 (0) 1708 25 35 50		
Email:	info@advance-cp.com		

1.4. Emergency telephone number

Emergency tel: +44 (0) 1282 834545 Mon - Fri: 08:30 - 16:30

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xn: R20/21; Xi: R38

Classification under CLP: Flam. Liq. 1: H224; Skin Irrit. 2: H315

Most important adverse effects: Highly flammable. Harmful by inhalation and in contact with skin. Irritating to skin.

2.2. Label elements

Label elements under CLP:

Hazard statements: H224: Extremely flammable liquid and vapour.

H315: Causes skin irritation.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



MOSS GREEN VINYLAST

		Page:	2	
Precautionary statements:	P243: Take precautionary measures against static discharge.			
	P264: Wash thoroughly after handling.			
	P280: Wear.			
	P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.			
	Rinse skin with.			
	P332+313: If skin irritation occurs: Get medical.			
	P370+378: In case of fire: Use for extinction.			
Label elements under CHIP:				
Hazard symbols:	Highly flammable.			
	Harmful.			
Risk phrases:	R11: Highly flammable.			
	R20/21: Harmful by inhalation and in contact with skin.			
	R38: Irritating to skin.			
Safety phrases:	S36/37: Wear suitable protective clothing and gloves.			
2.3. Other hazards				
Other hazards:	In use, may form flammable / explosive vapour-air mixture.			
PBT:	This substance is not identified as a PBT substance.			
ection 3 [.] Composition/information on ingredients				

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

XYLENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332;	30-50%
			Acute Tox. 4: H312; Skin Irrit. 2: H315	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	: Remove all contaminated clothes and footwear immediately unless stuck to skin.				
	Drench the affected skin with running water for 10 minutes or longer if substance is still				
	on skin. Consult a doctor.				
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.				
Ingestion:	Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water				
	to drink immediately. Consult a doctor.				
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a				
	doctor.				

MOSS GREEN VINYLAST

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

MOSS GREEN VINYLAST

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

 Handling requirements:
 Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

 Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State: Liquid
- Colour: Green
- Viscosity: Viscous
- **Boiling point/range°C:** <=35
 - pH: Approx. 7

Flash point°C: 23-31

MOSS GREEN VINYLAST

Page: 5

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

MOSS GREEN VINYLAST

Page: 6

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Marine pollutant: No

MOSS GREEN VINYLAST

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information				
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No			
	453/2010.			
	* indicates text in the SDS which has changed since the last revision.			
Phrases used in s.2 and 3:	H224: Extremely flammable liquid and vapour.			
	H226: Flammable liquid and vapour.			
	H312: Harmful in contact with skin.			
	H315: Causes skin irritation.			
	H332: Harmful if inhaled.			
	R10: Flammable.			
	R11: Highly flammable.			
	R20/21: Harmful by inhalation and in contact with skin.			
	R38: Irritating to skin.			
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive			
	and shall be used only as a guide. This company shall not be held liable for any			
	damage resulting from handling or from contact with the above product.			

[final page]

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

Southampton	Rainham	likeston	Birmingham	Haydock	Glasgow
Tel: 023 8070 3333	Tel: 01708 25 35 45	Tel: 0115 930 2070	Tel: 0121 565 8282	Tel: 01942 86 88 88	Tel: 0141 773 6699
Fax: 023 8070 5555	Fax: 01708 25 35 50	Fax: 0115 951 2455	Fax: 0121 565 8292	Fax: 01942 86 88 99	Fax: 0141 773 6633
F.H.BRUNDLE		www.fhbrundle.co.uk			
SERVING THE TRADE SINCE 1889		sales@brundle.com			