

PAINT SAFETY DATA SHEET



SAFETY DATA SHEET

BRUNDLE GREY PRIMER

Page: 1

Compilation date: 01/10/2020

Revision No: 1.1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BRUNDLE GREY PRIMER

Product code: 29ZQDP01, 29ZQDP05, 29ZQDP20

Synonyms: GREY

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: F.H. BRUNDLE

24-36 LAMSON ROAD FERRY LANE NORTH

RAINHAM ESSEX RM13 9YY

UK

Tel: +44 (0) 1708 25 35 45

Fax: +44 (0) 1708 25 35 59

Email: sales@brundle.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1282 834545 Mon-Fri: 08:30 - 16:30 www.fhbrundle.co.uk

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xn: R20/21; Xi: R38; N: R51/53

Classification under CLP: Eye Irrit. 2: H319; Aquatic Chronic 2: H411; Carc. 2: H351; Flam. Liq. 2: H225; Skin Irrit. 2:

H315

Most important adverse effects: Highly flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Toxic

to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation. H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

BRUNDLE GREY PRIMER

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard GHS09: Environmental









Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

P280: Wear.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical.

P370+378: In case of fire: Use for extinction.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.

Dangerous for the environment.







Risk phrases: R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Safety phrases: S36/37: Wear suitable protective clothing and gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Contains methyl ethyl ketoxime. May produce an allergic reaction.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

BRUNDLE GREY PRIMER

Page: 3

Hazardous ingredients:

ALKYD RESIN SOLUTION

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	-: R10; Xn: R20/21; Xi: R38	-	30-50%
XYLENE				
215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
ZINC PHOSPH	IATE			
231-944-3	7779-90-0	N: R50/53	-	1-10%
10% COBALT	DRIER			
-	-	Xn: R22; Xi: R38; Sens.: R43; Xn: R65	-	<1%
10% CALCIUN	I DRIER			
-	-	Xi: R38	-	<1%
METHYL ETHY	/L KETOXIME			
202-496-6	96-29-7	Xn: R21; Xn: R40; Xi: R41; Sens.: R43	-	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

BRUNDLE GREY PRIMER

Page: 4

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

BRUNDLE GREY PRIMER

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	-	-
ZINC PHOSPHATE				

10% CALCIUM DRIER

UK

UK	1000 mg/m3	_	_	_
l UN	1000 1119/1113	-	-	-

METHYL ETHYL KETOXIME

UK	10 mg/m3	_	_	_
OIX	TO HIG/IIIO	-	-	_

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

10 mg/m3

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Grey

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Viscosity: Viscous

Boiling point/range°C: >35 Flash point°C: 23-31

pH: Approx. 7

9.2. Other information

Section 10: Stability and reactivity

BRUNDLE GREY PRIMER

Page: 6

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

BRUNDLE GREY PRIMER

Page: 7

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

BRUNDLE GREY PRIMER

Page: 8

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R21: Harmful in contact with skin.

R22: Harmful if swallowed.

R38: Irritating to skin.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

[final page]

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

Southampton Tel: 023 8070 3333 Fax: 023 8070 5555 Rainham Tel: 01708 25 35 45 Fax: 01708 25 35 50 Ilkeston Tel: 0115 930 2070 Fax: 0115 951 2455 Birmingham Tel: 0121 565 8282 Fax: 0121 565 8292 Haydock Tel: 01942 86 88 88 Fax: 01942 86 88 99

Glasgow Tel: 0141 773 6699 Fax: 0141 773 6633

