PRODUCT NAME: Brundle Galvalast

PRODUCT CODE: 2903

PRODUCT DESCRIPTION

A Grey zinc rich brushing primer that is a very hard and durable, with excellent protective properties, for initial surface preparation underneath FH Brundle brushing primers and enamels. Used regularly on products that are subjected to heavy wear, such as machinery.

AVAILABILITY

This product is available in 400ml packs.

FURTHER INFORMATION

This product is specifically designed to be brushed or rolled. Can be thinned by up to 10% maximum. If overcoating is required, 24 hours minimum before application.

VISCOSITY	SPECIFIC GRAVITY	GLOSS
6-8 Poise @ Roto 20c	1.26-1.34 SPL	<5%

SURFACE PREPERATION AND APPLICATION

Make sure primed surface is free from dust, grease or any other contamination.

APPLICATION AIRLESS SPRAY

Brush or Foam Roller.

HEALTH & SAFETY

Refer to M.S.D.S. 29PC2903 prior to use. See: https://www.fhbrundle.co.uk/search?query=2903

Provide adequate ventilation. Prolonged skin contact inhalation of vapour must be avoided.

Eye contamination - Flush with eyewash or warm water for 10 mins. Clean hands after use.

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and F.H. Brundle can accept no liability for the performance of the product or for any loss or damage arising out of such use.

November 2022

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

Southampton Tel: 023 8070 3333 Fax: 023 8070 5555

BRUNDLE

Rainham Tel: 01708 25 35 45 Fax: 01708 25 35 50 likeston Tel: 0115 930 2070 Fax: 0115 951 2455

F H BRUNDLE

SERVING THE TRADE SINCE 1889

Birmingham Tel: 0121 565 8282 Fax: 0121 565 8292 Newton-Le-Willows Tel: 01942 86 88 88 Fax: 01942 86 88 99

Glasgow Tel: 0141 773 6699 Fax: 0141 773 6633

www.fhbrundle.co.uk sales@brundle.com

RECOMMENDED W.F.T.

125-150 microns

RECOMMENDED D.F.T. 60-80 microns

THEORETICAL SPREADING RATE 10-12 Sq. Metres/Litre

DRYING TIME @ 20°C Surface Dry: 4-6 hours

FLASH POINT 32-55°C VOC: 530 g/litre VOLUME SOLIDS 50% (-/+ 2%) THINNERS 29WS05 SHELF LIFE 12 Months