# TECHNICAL DATA SHEET

## PRODUCT NAME

Spray can topcoats for touch up

## PRODUCT DESCRIPTION

F.H Brundle supply a wide variety of aerosol spray cans which are available to help the customer finalise their finishing coat. These are used to cover any hard to reach places, plus to repair any small areas of damage which may have occurred during movement, transport or installation of goods.

## AVAILABILITY

This product is a 400m rattle can.

## FURTHER INFORMATION

On the next page is a list of all relevant spray cans supplied with relevant details.
*Due to the protective nature of the coating, some chalking may occur on exposure/weathering. This is aesthetic and will not deter from the performance of the product.

## SURFACE PREPERATION AND APPLICATION

Ensure surface is free from rust, moisture, oil, or other surface contamination.

## APPLICATION

Product should be applied at least 20cm away from surface and sprayed continuously at a fanning angle. To clean the nozzle, turn can upside down and spray until passageway is clear.

## RECOMMENDED W.F.T.

N/A

## RECOMMENDED D.F.T.

N/A

## THEORETICAL SPREADING RATE

1.5-3 Sq. Metres/Litre

## DRYING TIME @ 20°C

Surface Dry: 10-20 minutes

**FLASH POINT:**
**VOC:** N/A
**VOLUME SOLIDS:** N/A
**THINNERS:** N/A
**SHELF LIFE:** 12 Months

## HEALTH & SAFETY

Refer to Spray can M.S.D.S. prior to use. These can be found under the relevant Product Codes on https://www.fhbrundle.co.uk/

Provide adequate ventilation. Prolonged skin contact inhalation of vapour must be avoided.

Eye contamination - Flush with eyewash or warm water for 10 mins.

Always clean hands after use.

Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and F.H. Brundle can accept no liability for the performance of the product or for any loss or damage arising out of such use.

| PRODUCT CODE | PRODUCT NAME | COLOUR | GLOSS LEVEL |
|---|---|---|---|
| 29RSBS | Smithy Black Semi-Gloss Vinylast | Black | 20-30% |
| 29RMBS | Smithy Matt Black Vinylast | Black | <5% |
| 29RGBS | Smithy Gloss Black Vinylast | Black | >70% |
| 29RSWS | Smithy White Vinylast | RAL 9010 | 20-30% |
| 29PC400SG | Fortitude Green Gloss Aerosol | RAL 6005 | 40-50% |
| 29PC400SB | Fortitude Black Gloss Aerosol | RAL 9005 | 40-50% |
| 29PC400SBS | Fortitude Black Sand Aerosol | Specialist | 40-50% |
| 29PC400SW | Fortitude White Gloss Aerosol | RAL 9010 | 40-50% |
| 29PC400SSY | Yellow Gloss | RAL 1003 | >70% |
| 29PC400SA | Anthracite Gloss | RAL 7012 | >70% |
| 29PC400SAM | Basalt Matt | RAL7012 | <5% |
| 29PC400SLS | Light Sage Matt | RAL 7032 | <5% |
| 29PC400SUG | Umbra Matt | RAL 7022 | <5% |
| 29PC400SMG | Mineral Grey Matt | RAL 7045 | <5% |
| 29PC400SSS | Serengeti Sand Matt | RAL 1019 | <5% |
| 29PC400SOW | Oyster White Matt | RAL 1013 | <5% |
| 29PC400STB | Terra Brown Matt | RAL 7028 | <5% |
| 29PC400SSSG | Serengeti Sand Gloss | RAL 1019 | >70% |
| 29PC400SSSY | Serengeti Sand Synergised | RAL 1019 | <5% (textured) |
| 29PC400SBSY | Black Synergised | RAL 9005 | <5% (textured) |
| 29PC400SASY | Anthracite Synergised | RAL 7016 | <5% (textured) |

*12/05/2022*

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

**Southampton** Tel: 023 8070 3333 Fax: 023 8070 5555
**Rainham** Tel: 01708 25 35 45 Fax: 01708 25 35 50
**Ilkeston** Tel: 0115 930 2070 Fax: 0115 951 2455
**Birmingham** Tel: 0121 565 8282 Fax: 0121 565 8292
**Haydock** Tel: 01942 86 88 88 Fax: 01942 86 88 99
**Glasgow** Tel: 0141 773 6699 Fax: 0141 773 6633

BRUNDLE
F.H.BRUNDLE
SERVING THE TRADE SINCE 1889
www.fhbrundle.co.uk
sales@brundle.com