





This 1.8m x 4M sliding track gate is delivered as two individual frames. The frames need to be welded and bolted together on site. The floor tracks then need cutting to a total length of 9365mm before fitting so it matches the total rolling distance of the gate. Goal posts, pales & gate fittings are provided so the gate can be fully assembled onsite.

CODE	DESCRIPTION	
0587504000	3 metre Track for 20mm Round Grvd Wheels in Galvanised Steel.	
0515094	20 x 20mm T Wheel With Internal Support Round Groove	4
05SBS06	Plastic/Metal Bump Stop 50mm Diameter Anti Vibration	2
05GD118	Upper Guide Roller - Nylon For Use With Sliding Gates	4
N/A	M24 x 140 Galvanised Hex Head Bolt & Nuts	4

PART CODE	MATERIAL	FINISH	COLOUR
54SGB184RG	Mild Steel	Galvanised	GREEN
54SGB184RB	Mild Steel	Galvanised	BLACK

DECODIDITION AND DELLID		4 \A/' T O A	DILO
DESCRIPTION: Mesh Bolt Down Ti	rack Silaina (zate – i X	Y AM WITH ITACK X. ACCES	SOMES - RH ()DENING
DESCRIPTION, MICSELDON DOWN IN	ack sliding date 1.0	A TITL MILL HACK & ACCC	SOLICS KIT OPCILLING

	NAME	DATE	REVISION	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS		
DRAWN	GC	26/05/2021	Α			A3
CHECKED				DO NOT SCALE DRAWING	SCALE:1:40	