





CUT & STITCH WELD TRACK TO FRAME

5300

This 1.8m x 4M cantilever gate is delivered as two individual frames with a uncut gate track. The frames need to be welded and bolted together on site. The track then needs cutting before stitch welding to the bottom of the assembled gate frame. Goal posts & gate fittings provided so the gate can be fully assembly onsite.

CODE	DESCRIPTION	
67CGS3508P	Piccolo 350 - 8 Wheel Carriage for 8.0m Maximum Opening - Galvanised	2
67CGS346P	End Stop for Piccolo 250 and 350 Galvanised	2
39021020	Guide Roller Medium Series (8 Metre Max Opening)	2
05GD118	Upper Guide Roller - Nylon For Use With Sliding Gates	4
67CGS345P6G	Piccolo 350 Track - Galvanised 6m	1
N/A	M24 x 140 Galvanised Hex Head Bolt & Nuts	4

PART CODE	MATERIAL	FINISH	COLOUR	
54SGC184LG	Mild Steel	Galvanised	GREEN	
54SGC184LB	Mild Steel	Galvanised	BLACK	

s - LH Opening	Cantilever Sliding Gate - 1.8 x 4M With Track & Accessories - LH	
3 - LI I	Carrille vol silaling Gate - 1.0 x 4/vi vviiri Irack & //cccssories - El	-

	NAME	DATE	REVISION	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS		
DRAWN	GC	24/05/2021	Α			A3
CHECKED				DO NOT SCALE DRAWING	SCALE:1:40	