





CUT & STITCHS WELD TRACK TO FRAME

5300

This 1.8m x 4M cantilever gate is delivered as two individual frames with a uncut gate track. The frames need to be welded and bolted together on site. The track then needs cutting before stitch welding to the bottom of the assembled gate frame. Goal posts & gate fittings provided so the gate can be fully assembled onsite.

					AAATEDIAI	EIVIICLI	
CODE	DESCRIPTION	QTY		PART CODE	MATERIAL	FINISH	COLOUR
				54SGC184RG	Mild Steel	Galvanised	GREEN
67CGS3508P	Piccolo 350 - 8 Wheel Carriage for 8.0m Maximum Opening - Galvanised	2		J43GC104NG	Milia sieei	Galvarisea	GILLIN
		_		54SGC184RB	Mild Steel	Galvanised	BLACK
67CGS346P	End Stop for Piccolo 250 and 350 Galvanised	2	L	9430C104KB	74110 31001	Odivariisca	DL/ (CI
	·	_					
39021020	Guide Roller Medium Series (8 Metre Max Opening)	2					

DESCRIPTION: Mesh Cantilever Sliding Gate - 1.8 x 4M With Track & Accessories - RH Opening								
	CIFIED	REVISION	DATE	NAME				
A3	<i>IILLIMETERS</i>	Α	24/05/2021	GC	DRAWN			
	SCALE:1:40	DO NOT SCALE DRAWING				CHECKED		

CODE	DESCRIPTION	ווא	
67CGS3508P	Piccolo 350 - 8 Wheel Carriage for 8.0m Maximum Opening - Galvanised	2	
67CGS346P	End Stop for Piccolo 250 and 350 Galvanised	2	
39021020	Guide Roller Medium Series (8 Metre Max Opening)	2	
05GD118	Upper Guide Roller - Nylon For Use With Sliding Gates	4	
67CGS345P6G	Piccolo 350 Track - Galvanised 6m	1	
N/A	M24 x 140 Galvanised Hex Head Bolt & Nuts	4	