TECHNICAL DATA SHEET



4500 ACRYLIC BASE COATING

Description 4500 Acrylic Base Coating is a fast drying, spray coating used

for metal or wood furniture decoration. To protect the coating, a

protective clear coat should be applied.

Surface Preparation Surfaces should be smooth without areas of fur, evenly

pre-sanded with no coarser than 150 grit paper. The surface must be free from contaminating waxes, oils and silicones.

Previously Painted Surfaces Surface to be painted must be thoroughly clean, dry and free

from dirt, grease and loose or flaky coating. All paint works must be scrapped off and defective areas should be sanded down

and spot primed with appropriate filler before painting.

Physical Properties

Vehicle Type Single Pack Acrylic

Pigmentation Colouring

Solvent S303 or S4008 thinner

Mixing Ratio Single pack

Density 1.00 - 1.20

Flash Point Approximately 25 - 30°C

Theoretical Coverage 15 m² / litre

Drying Time at $(27 \pm 2^{\circ}C)$ Surface Dry ≤ 5 mins

Touch Dry \leq 10 mins Hard Dry \leq 30 mins

Colours Copper gold, gold, duchess gold & silver

Finish Semi-gloss

Dilution If necessary use S303 or S4008 thinner

Storage Condition Air tight, store in dry and cool conditions below 30°C

Shelf Life 12 months (min) in full sealed containers stored in a cool

condition

Packing 5 litres

Application Temperature 5 - 40°C

Application Method Spray, dipping or rubbing

Thinning Use as supplied, but stir the material thoroughly before use

and occasionally during application

Equipment Wash S303 thinner

Product Identification

This technical data sheet covers the following product codes and names:

Code: 0599900010 - 250ml of Copper Patina
Code: 0599900011 - 250ml of Gold Patina
Code: 0599900012 - 250ml of Green Patina
Code: 0599900013 - 250ml of Silver Patina Paint
Code: 0599900017 - 250ml of Old Copper Patina
Code: 0599900018 - 250ml of Bronze Gold Patina

Product Liability

The Seller warrants the product to be free from manufacturing defects in material and workmanship. The Seller's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited at the Seller's option, to either replacement of products not conforming to this warranty or credit to the Buyer's account in the invoiced amount of the non-conforming products.

The Seller makes no other warranties concerning this product. No other warranties, either express or implied, or satisfactory, and as warranties or merchantability or fitness for a particular purpose, shall apply. In no event shall the Seller be liable for consequential or incidental damages. Any recommendations or suggestion relating to the use of the products made by the Seller, whether in its technical limitation, or in response to specific inquiry, or otherwise, is based on data believed to be reliable, however, the products and information are intended for Buyers having requisite skill and know-how in the industry, and therefore it is for the Buyer to satisfy itself of the suitability of the products for its own particular use, and it shall be deemed that the Buyer has done so, at its sole discretion and risk. Variation in environment changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H.Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Application must be carried out in full compliance with current regulations. Please consult the relevant Safety Data Sheet (SDS) for further information. F.H.Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.

Southampton

Rainham

Ilkeston

Birmingham

Haydock

Edinburgh

Glasgow

Tel: 023 8070 3333 Fax: 023 8070 5555 Tel: 01708 25 35 45 Fax: 01708 25 35 50 Tel: 0115 930 2070 Fax: 0115 951 2455 Tel: 0121 565 8292 Fax: 0121 565 8292 Tel: 01942 86 88 88 Fax: 01942 86 88 99

Tel: 0131 335 5999 Fax: 0131 335 5911 Tel: 0141 332 3231 Fax: 0141 332 7325

